


HIGH TENSILE SHACKLES

HIGH TENSILE DEE SHACKLE type A (screw pin)

CHAIN SLINGS G80

WIRE ROPE SLINGS

- standard: U.S. Federal Specification RR-C-271 (similar to EN 13889)
- material: drop forged high tensile steel, quenched and tempered
- surface finish: body: galvanized
pin: yellow painted
- applications: chain and wire rope slings, general
- safety factor: 4:1
- marking: *WLL *size (in inches) *CE



code	size	WLL	A	B	C	D	H	L	weight [kg/pcs]
	[inch]	[T]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	
SZAWA005	1/4	0,50	8	18	42	8	22	12	0,05
SZAWA0075	5/16	0,75	9	21	49	9,5	27	13	0,08
SZAWA010	3/8	1,00	10	25	57	11	31	16	0,13
SZAWA015	7/16	1,50	11	27	65	12	37	18	0,18
SZAWA020	1/2	2,00	12	31	80	16	44	21	0,28
SZAWA032	5/8	3,25	16	38	95	19	50	28	0,55
SZAWA047	3/4	4,75	19	47	120	22	68	33	0,95
SZAWA065	7/8	6,50	22	52	132	25	72	36	1,45
SZAWA085	1	8,50	26	59	150	28	79	42	2,10
SZAWA095	1 1/8	9,50	29	65	175	32	92	45	2,90
SZAWA120	1 1/4	12,00	34	76	185	35	95	50	4,00
SZAWA170	1 1/2	17,00	39	89	230	41	118	63	6,90