

ZACISKI LINOWE OCYNKOWANE

ZACISK LINOWY KABŁĄKOWY wg DIN 741 ocynkowany

symbol	rozmiar nominalny	na linę [φ]	L	B	waga
	[mm]	[mm]	[mm]	[mm]	[kg/szt]
ZL03	3	2,5-3,0	5	18	0,008
ZL05	5	3,0-5,0	7	22	0,013
ZL065	6,5	5,0-6,5	8	24	0,016
ZL08	8	6,5-8,0	10	29	0,028
ZL10	10	8,0-10,0	11	34	0,057
ZL11	11	10,0-11,0	11	34	0,058
ZL13	13	11,0-13,0	14	41	0,112
ZL14	14	13,0-14,0	14	44	0,116
ZL16	16	14,0-16,0	18	49	0,190
ZL19	19	16,0-19,0	20	54	0,240
ZL22	22	19,0-22,0	23	62	0,364
ZL26	26	22,0-26,0	29	65	0,393
ZL30	30	26,0-30,0	33	76	0,594
ZL34	34	30,0-34,0	37	81	0,732
ZL40	40	34,0-40,0	43	87	0,930
ZL45	45	40,0-45,0	48	110	1,430
ZL50	50	45,0-50,0	62	115	1,830

