

KAUSZE OCYNKOWANE

KAUSZA wg DIN 6899 B ocynkowana

symbol	rozmiar nominalny	na linę [φ]	L	H	B	waga
	[mm]	[mm]	[mm]	[mm]	[mm]	[kg/szt]
KA03	3	2,5-3,0	12	19	3	0,006
KA04	4	3,0-4,0	13	21	4	0,007
KA05	5	4,0-5,0	14	23	5	0,009
KA06	6	5,0-6,0	16	25	6	0,013
KA08	8	7,0-8,0	20	31	8	0,027
KA10	10	8,0-10,0	23	39	10	0,037
KA12	12	10,0-12,0	28	44	12	0,066
KA14	14	12,0-14,0	32	53	14	0,081
KA16	16	14,0-16,0	36	58	16	0,126
KA18	18	16,0-18,0	40	64	18	0,229
KA20	20	18,0-20,0	45	72	20	0,298
KA22	22	20,0-22,0	48	78	22	0,347
KA24	24	22,0-24,0	53	88	24	0,659
KA26	26	24,0-26,0	60	99	26	0,729
KA28	28	26,0-28,0	65	111	28	0,887
KA30	30	28,0-30,0	75	120	30	0,949
KA32	32	30,0-32,0	78	124	32	1,120

