


KAUSZE OCYNKOWANE

KAUSZA wg DIN 6899 B ocynkowana

symbol	rozmiar nominalny	na linę [φ]	L	H	waga
	[mm]	[mm]	[mm]	[mm]	[kg/szt]
KA03	3	2,5-3,0	12	19	0,006
KA04	4	3,0-4,0	13	21	0,007
KA05	5	4,0-5,0	14	23	0,009
KA06	6	5,0-6,0	16	25	0,013
KA08	8	7,0-8,0	20	31	0,027
KA10	10	8,0-10,0	23	39	0,037
KA12	12	10,0-12,0	28	44	0,066
KA14	14	12,0-14,0	32	53	0,081
KA16	16	14,0-16,0	36	58	0,126
KA18	18	16,0-18,0	40	64	0,229
KA20	20	18,0-20,0	45	72	0,298
KA22	22	20,0-22,0	48	78	0,347
KA24	24	22,0-24,0	53	88	0,659
KA26	26	24,0-26,0	60	99	0,729
KA28	28	26,0-28,0	65	111	0,887
KA30	30	28,0-30,0	75	120	0,949
KA32	32	30,0-32,0	78	124	1,120



KAUSZE NIERDZEWNE

KAUSZA wg DIN 6899B nierdzewna AISI 316

symbol	rozmiar nominalny	na linę [φ]	L	H	waga
	[mm]	[mm]	[mm]	[mm]	[kg/szt]
NKA03	3	2,5-3,0	11	22	0,002
NKA04	4	3,0-4,0	13	27	0,005
NKA05	5	4,0-5,0	14	27	0,005
NKA06	6	5,0-6,5	16	31	0,007
NKA08	8	6,5-8,0	18	37	0,013
NKA10	10	8,0-10,0	22	46	0,026
NKA12	12	10,0-12,0	27	54	0,035
NKA14	14	12,0-14,0	34	56	0,085
NKA16	16	14,0-16,0	36	72	0,114

