

GRADE 6 SHACKLES

HIGH TENSILE BOW SHACKLE type C EN13889

| | |
|-----------------|---|
| standard: | EN13889 |
| material: | drop forged high tensile (alloy) steel, quenched and tempered |
| surface finish: | body: galvanized; pin: yellow painted |
| safety factor: | 4:1 |
| body marking: | *manufacturer code *batch number *working load limit (WLL) *class number 6 *dimension in inches *CE |
| pin marking: | *class number 6 *manufacturer code *batch number |
| usage: | general use |

| code | size | WLL | A | B | C | D | H | L | R | weight |
|----------|-------|-------|------|------|------|------|------|------|------|----------|
| | [cal] | [T] | [mm] | [mm] | [mm] | [mm] | [mm] | [mm] | [mm] | [kg/pcs] |
| SZAQC020 | 1/2 | 2,00 | 12 | 31 | 83 | 16 | 47 | 21 | 17 | 0,33 |
| SZAQC032 | 5/8 | 3,25 | 16 | 38 | 106 | 19 | 61 | 28 | 21 | 0,65 |
| SZAQC047 | 3/4 | 4,75 | 19 | 47 | 124 | 22 | 71 | 33 | 25 | 1,08 |
| SZAQC065 | 7/8 | 6,50 | 22 | 53 | 141 | 25 | 83 | 36 | 28 | 1,65 |
| SZAQC085 | 1 | 8,50 | 25 | 59 | 165 | 28 | 94 | 42 | 33 | 2,42 |
| SZAQC095 | 1 1/8 | 9,50 | 29 | 64 | 185 | 32 | 105 | 44 | 36 | 3,41 |
| SZAQC120 | 1 1/4 | 12,00 | 33 | 76 | 205 | 35 | 117 | 48 | 40 | 4,83 |
| SZAQC170 | 1 1/2 | 17,00 | 39 | 89 | 255 | 41 | 145 | 63 | 48 | 8,24 |

