


MASTER LINKS

MASTER LINK A for one- and two-leg slings EN1677-4

GRADE 8 ACCESSORIES FOR CHAIN SLINGS

standard:	EN1677-4
surface finish:	red painted
safety factor:	4:1
marking:	*manufacturer's code *traceability code *code number *(WLLxx.xx T) *grade number (chain size.8) *CE
usage:	for one- and two-leg slings; for lifting purposes




code	link size	chain 1-leg sling	chain 2-leg sling	WLL	A	B	C	weight
	[φ]	[mm]	[mm]	[T]	[mm]	[mm]	[mm]	[kg/pcs]
OGA13	A14	6-7	6	1,60	90	61	108	0,40
OGA16	A16	8	7	2,12	91	59	109	0,53
OGA18	A18	10	8	3,15	111	75	136	0,82
OGA22	A22	13	10	5,30	134	90	162	1,46
OGA26	A26	16	13	8,00	155	103	184	2,17
OGA32	A32	18	16	11,20	175	111	200	3,92
OGA36	A36	20	18	14,00	212	140	253	6,31
OGA40	A40		20	17,00	245	155	305	9,00

MASTER LINK A for one- and two-leg slings EN1677-4

GRADE 10 ACCESSORIES FOR CHAIN SLINGS

standard:	EN1677-4
surface finish:	blue painted
safety factor:	4:1
marking:	*manufacturer's code *traceability code *code number *(WLLxx.xx T) *grade number (chain size.10) *CE
usage:	for one- and two-leg slings; for lifting purposes




code	link size	chain 1-leg sling	chain 2-leg sling	WLL	A	B	C	weight
	[φ]	[mm]	[mm]	[T]	[mm]	[mm]	[mm]	[kg/pcs]
XOGA16	A16	8	-	3,50	98	56	110	0,55
XOGA18	A18	10	8	5,00	118	70	135	0,83
XOGA22	A22	13	10	7,60	140	83	160	1,48
XOGA26	A26	16	13	10,00	160	93	180	2,50

MASTER LINK ASSEMBLY M for three- and four-leg slings EN1677-4

GRADE 8 ACCESSORIES FOR CHAIN SLINGS

standard:	EN1677-4
surface finish:	red painted
safety factor:	4:1
marking:	*manufacturer's code *traceability code *code number *(WLLxx.xx T) *grade number (chain size.8) *CE
usage:	for three- and four-leg slings; for lifting purposes




code	link size	chain 3- 4-leg sling	WLL	A	B	C	D	E	F	weight
	[φ]	[mm]	[T]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[kg/pcs]
OGM1813	18-14	6-7	3,15	108	72	135	65	60	37	1,32
OGM2216	22-16	8	4,25	135	89	157	66	72	34	2,18
OGM2618	26-18	10	6,70	150	98	184	73	86	37	3,22
OGM3222	32-22	13	11,20	176	112	200	94	118	50	6,04
OGM3626	36-26	16	17,00	212	140	250	119	145	67	9,70
OGM5132	51-32	20	26,50	290	190	350	170	180	100	23,90

MASTER LINK ASSEMBLY M for three- and four-leg slings EN1677-4**GRADE 10 ACCESSORIES FOR CHAIN SLINGS**


standard: EN1677-4
 surface finish: blue painted
 safety factor: 4:1
 marking: *manufacturer's code *traceability code *code number *(WLLxx.xx T)
 *grade number (chain size.10) *CE
 usage: for three- and four-leg slings; for lifting purposes

code	link size	chain 3- 4-leg sling	WLL	A	B	C	D	E	F	weight
	[ϕ]	[mm]	[T]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[kg/pcs]
XOGM2216	22-16	8	5,30	134	88	155	69	70	30	2,21
XOGM2618	26-18	10	8,00	154	100	180	78	85	35	3,60
XOGM3222	32-22	13	14,00	170	108	195	99	115	46	6,10

**MASTER LINK ASSEMBLY N ENLARGED for three- and four-leg rope slings****GRADE 8**


surface finish: red painted
 safety factor: 4:1
 marking: *manufacturer's code *traceability code *code number *(WLLxx.xx T)
 *grade number *CE
 usage: for three- and four-leg slings; for lifting purposes

code	link size	steel wire rope 3- 4-leg sling	WLL	A	B	C	D	E	F	weight
	[ϕ]	[mm]	[T]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[kg/pcs]
OGN1814	18-14	12-14	4,60	93	61	120	88	120	60	1,43

**CONNECTING LINKS****CONNECTING LINK EN1677-1****GRADE 8 ACCESSORIES FOR CHAIN SLINGS**

standard: EN1677-1
 surface finish: red painted
 safety factor: 4:1
 marking: *manufacturer's code *traceability code *code number *(WLLxx.xx T)
 *grade number (chain size.8) *CE
 usage: for slings; for lifting purposes; for general use

code	chain	WLL	A	B	C	D	E	weight
	[mm]	[T]	[mm]	[mm]	[mm]	[mm]	[mm]	[kg/pcs]
ŁCON06	6	1,12	41	15	8	15	42	0,08
ŁCON078	7-8	2,00	53	20	11	23	59	0,15
ŁCON10	10	3,15	66	25	13	28	71	0,33
ŁCON13	13	5,30	82	30	16	31	86	0,68
ŁCON16	16	8,00	98	35	18	40	109	1,22
ŁCON20	20	12,50	114	41	21	45	116	1,96

**CONNECTING LINK EN1677-1****GRADE 10 ACCESSORIES FOR CHAIN SLINGS**

standard: EN1677-1
 surface finish: blue painted
 safety factor: 4:1
 marking: *manufacturer's code *traceability code *code number *(WLLxx.xx T)
 *grade number (chain size.10) *CE
 usage: for slings; for lifting purposes; for general use

code	chain	WLL	A	B	C	D	E	weight
	[mm]	[T]	[mm]	[mm]	[mm]	[mm]	[mm]	[kg/pcs]
XLCON08	8	2,50	54	19	10	25	62	0,19
XLCON10	10	4,00	67	24	13	27	70	0,33
XLCON13	13	6,70	83	27	17	36	91	0,72

